

<b>MARKETING</b>	
<b>Model Number</b>	APFD06JASW
<b>Description</b>	GE® 6,100 BTU Portable Air Conditioner with Dehumidifier and Remote, White
<b>Commercial Category</b>	Room Air Conditioners_Portable
<b>Base Model</b>	APFD06JASW
<b>Color</b>	
<b>Brand</b>	GE
<b>Derivative Type</b>	
<b>Estimated Retail Price</b>	0.00
<b>UPC</b>	084691861218
<b>Product Status</b>	Active
<b>First Distribution Date</b>	2020/11/12 12:00:00
<b>Full ADC Availability Date</b>	2021/03/01 12:00:00
<b>Final Production Date</b>	2025/04/30 12:00:00
<b>Manufacturing Location</b>	

## OVERVIEW

### FEATURES

Product Type	Portable
Refrigerant Type	R410A
Power Cord Length	6'
Plug Type	A / 5-15P
Fan Speed Selections	2 Cooling/2 Fan with Eco Mode
Mounting Type	
	Easy Access
Filter Type	Permanent Mesh
Area to Cool	
Chassis Type	
LCDI / AFCI power cord	Yes
Room Air Conditioner Features	
Rotary Compressor	
Thermostat Type	Thermistor
Unit Type	
Vent/Air Exchange Exhaust	Front Air Discharge
EER	6.8
Louver Style	
	Left & Right
Airflow Direction	Up & Down
Airflow (cfm) Roomside	210/170
WiFi Connect	
Connected Capabilities	
Remote Control	Yes

Delay Timer	Yes
Digital Time Temp Display	Blue LED
Control Type	Tactile touch pad with LED Display
Operating Temperature Range F	68-80
	24 hr. On/Off Timer
	Auto Restart
	Dehumidify Function
Unit Features	Remote Control
Plug Capacity	120V/15A
Airflow Configuration	Single-hose
Exhaust Hose Length	5
Window Exhaust Kit	Yes
Continuous Condensate Drain	Yes
Self-Evaporative	Yes
Room Size (Sq Ft)	250

### **CAPACITY**

Dehumidification (pts./hr.)	
Cooling BTUH (MAX)	6100.000000
Dehumidification (pts./day)	55

### **APPEARANCE**

Installation	Extended Length Window Kit - 20" - 48"
Color Appearance	White
Easy-Roll Casters	Yes

### **WEIGHTS & DIMENSIONS**

Overall Depth	13 3/10
Overall Height	27 1/2
Overall Width	13 9/10
Approximate Shipping Weight	50 7/10
Net Weight	44 1/10
Minimum Window Opening Height (in.)	5
Min./Max. Window Opening Width (in.)	20/48

### **POWER / RATINGS**

CEER	
Cooling - Rated Cooling Amps AHAM	8.8
Cooling - Watts	1000
Sound Level (Low/High)	55 dbA
Voltage (MAX)	
Volts/Hertz	115V
Electrical Requirements	115V

Watts	1000
Hertz	60

**WARRANTY**

Labor Warranty  
Parts Warranty  
Warranty Notes

No Warranty  
1-Year Replacement  
See written warranty for full details

**CERTIFICATIONS**

Claims & Certifications

ASHRAE 128  
CUL  
RoHS Compliant  
UL  
California Prop 65  
CSA

**ECONOMICAL / QUIET**

Sound Level (dBA)  
Energy Saver  
Quiet Package

55 dBA

**ACCESSORIES**

**MISCELLANEOUS**

**FILTER**

**Primary Product Photo**

163459.jpg

**Additional Product and Feature Photos**

AWFS06BWL\_Spin\_R01\_C01.jpg  
AWFS06BWL\_Spin\_R01\_C02.jpg  
AWFS06BWL\_Spin\_R01\_C03.jpg  
AWFS06BWL\_Spin\_R01\_C04.jpg  
AWFS06BWL\_Spin\_R01\_C05.jpg  
AWFS06BWL\_Spin\_R01\_C06.jpg  
AWFS06BWL\_Spin\_R01\_C07.jpg  
AWFS06BWL\_Spin\_R01\_C08.jpg  
AWFS06BWL\_Spin\_R01\_C09.jpg  
AWFS06BWL\_Spin\_R01\_C10.jpg  
AWFS06BWL\_Spin\_R01\_C11.jpg  
AWFS06BWL\_Spin\_R01\_C12.jpg  
AWFS06BWL\_Spin\_R01\_C13.jpg  
AWFS06BWL\_Spin\_R01\_C14.jpg  
AWFS06BWL\_Spin\_R01\_C15.jpg  
AWFS06BWL\_Spin\_R01\_C16.jpg  
AWFS06BWL\_Spin\_R01\_C17.jpg  
AWFS06BWL\_Spin\_R01\_C18.jpg  
AWFS06BWL\_Spin\_R01\_C19.jpg  
AWFS06BWL\_Spin\_R01\_C20.jpg  
AWFS06BWL\_Spin\_R01\_C21.jpg  
AWFS06BWL\_Spin\_R01\_C22.jpg  
AWFS06BWL\_Spin\_R01\_C23.jpg  
AWFS06BWL\_Spin\_R01\_C24.jpg